



Insight Technology Pvt. Ltd.
UN Park, Jwagal, Lalitpur
Phone : 01 5260730
Cell: 9841538467 [whatsApp, Viber]
Sales : 9801148550
E-mail: care@insightinfosys.com
Web: <http://insightinfosys.com/>

Specification

Mimosa PoE Injector 24V (Power Over Ethernet)

| | |
|-----------------------|---|
| Model | Gigabit PoE Injector (24 V) |
| Part Number | 502-00025 |
| Dimensions | 97 mm x 53.5 mm x 35.5 mm (3.8" x 2.1" x 1.4") L x W x H |
| Weight | 0.13 kg (4.6 oz) |
| Color | Grey |
| Gigabit LAN | Yes, (2) RJ-45 |
| Output Voltage | 24 v === 0.5A |
| Max Current Load | 0.5A (12 W) |
| 2-Pair Powering | PIN 1/2 and 4/5: +24 V PIN 3/6 and 7/8: GND |
| Input Voltage | 100-240 VAC ~ 50/60 Hz; Max 0.75A |
| Input Current | 0.5A @ 90 VAC |
| Input Frequency | 47-63 Hz |
| Max In-Rush Current | 70A @ 230 VAC |
| Ripple Voltage | 120 mV |
| Protection | Over Current; Over Voltage |
| Efficiency | 82+% - Level VI |
| RJ-45 Type | Metal-Shielded |
| AC Connector | IEC-320 C6 (3 Pin Inlet) Corresponding Mimosa regional cords: 501- 094 (USA) (oo) 501-00095 (EU) 501-00097 (UK) |
| Operation Indicator | 1 LED (blue) |
| Operating Temperature | 0° C to +40° C |
| Operating Humidity | 10% to 90% non-condensing |
| Storage Temperature | -20° C to +80° C |
| Compliance | EMI FCC Part 15 Class B EN 55022/24 Class B / CE IEC61000-4 Safety UL/cUL 60950-1 GB4939 TUV:GS IEC60905 RCM/C-Tick S-Mark NOM Others WEEE/RoHS |